



## **USER MANUAL**

# **Digital to Analog Audio Converter with Volume Control**

### **Table of Contents**

1.0 Introduction .....	1
2.0 Specifications.....	2
3.0 Package Contents.....	3
4.0 Panel Descriptions.....	3
5.0 Connection and Operation.....	4

## **Dear Customer**

Thank you for purchasing this Audio Converter.

For optimum performance and safety, please read these instructions carefully before connecting, operating or adjusting this product. Please keep this manual for future reference

### **1.0 Introduction**

This Digital to Analog Audio Converter is designed for either home or professional audio switching. It converts Coaxial or Toslink digital audio signals to analog L/R audio and available for connection to an external device such as an amplifier via standard RCA-style jacks. This Converter is small in size and quite easy to install. Also it add the volume control function.

### **1.1 Features**

This Converter has many features that enable it to perform in a superior manner.

Among those features you will find:

1. Converts Coaxial or Toslink digital audio signals to analog L/R audio.
2. Supports sampling rate at 32, 44.1, 48 and 96 KHz.
3. 24-bit SPDIF incoming bit stream on left and right channels.
4. Provides electromagnetic-noise-free transmission.
5. Easy to install and simple to operate.
6. With Volume Control function.

## 2.0 SPECIFICATIONS

Signal Inputs/Output	
Input Audio	Coaxial or Toslink digital audio
Output Audio	L/R audio and 3.5mm
Connector	
Input audio connector	Toslink、 1XRCA(Coaxial)
Output audio connector	2XRCA (R/L) + Headphone
Sampling rate	32, 44.1, 48 and 96 KHz
Size(L-W-H)	72(D)x55(W)x20(H)>
Weight (Net)	<78g>
Power Requirement	
External Power Supply	5V DC@<1A>
Power Consumption	0.5 watts (max)

### 3.0 PACKAGE CONTENTS

Before attempting to use this unit, please check the packaging and make sure the following items are contained in the shipping carton:

- 1).Main unit (Digital to Analog Audio Converter).
- 2).DC 5V Power Supply.
- 3).User’s Manual.

### 4.0 PANEL DESCRIPTIONS



- 1 Toslink Input
- 2 Coaxial Input
- 3 DC/5V Power
- 4 Volume Control
- 5 Audio Output
- 6 Status of Power Input
- 7 Right Output
- 8 Left Output

## 5.0 CONNECTION AND OPERATION

Before installation, please make sure all devices you wish to connect have been turned off.

- 1) Connect the audio source device to the Converter using appropriate Toslink or Coaxial cables.
- 2) Connect the A/V Receivers or Amplifiers to the Converter using appropriate L/R cable.
- 3) Insert the DC side of 5v power supply into the converter and then connect the AC side of the power supply into the wall outlet.

Note: When connected to the Toslink and Coaxial cables at the same, the product will give priority to Toslink input.

